SKE Bharat | Specification sheet

Wound Close Type Motor

Wound Close Type Motor | SKU SKE-MOT-017

Slip-ring induction motors in a totally enclosed enclosure for dusty or damp heavy-duty applications. Also searched as: slip ring motor TEFC, totally enclosed slip ring motor, wound rotor motor TEFC, closed type slip ring motor, enclosed wound rotor induction motor

Specification

Motor Type	AC induction, slip-ring
Standard	IEC 60034
Enclosure / Protection	TEFC, IP55
Mounting	B3 foot / B5 flange / B35 foot-cum-flange
Duty	S1 / S3
Voltage Class	LT: 415 V, 3-phase, 50 Hz
Rotor	Wound (slip-ring)

Typical applications

- Dusty heavy-duty plants
- Hoists and lifts
- High-inertia drives

Key features

- Enclosed slip-ring housing protects brushes from dust
- High starting torque with low inrush
- Suitable for outdoor use with canopy

To get a quotation, send us

- Rated power (kW) and speed / poles
- Supply voltage, frequency and starting method (DOL / star-delta / soft starter / VFD)
- Mounting arrangement, frame and shaft details
- Enclosure, ambient temperature and hazardous-area classification
- Duty cycle (continuous / intermittent) and load type

Request a quotation

skebharat.com/product/wound-close-type-motor/

+91 88844 93900 | yeswanth@skebharat.com | Rajaji Nagar, Bangalore

SKE Bharat (SBYKSF Private Limited)

Summarised from the product page at skebharat.com. Ratings, standards and dimensions are confirmed in your quotation.